

"Typical test programs recommend that wrist straps that are used daily should be tested daily. However, if the products that are being produced are of such value that knowledge of a continuous, reliable ground is needed, and then continuous monitoring should be considered or even required." (ESD Handbook TR 20.20 section 5.3.2.4.4)

"All personnel shall be bonded or electrically connected to the grounding / equipotential bonding system when handling ESDS [ESD sensitive] items." (ANSI/ESDS20.20-2007 section 8.1)

"When personnel are seated at ESD protective workstations, they shall be connected to the grounding / equipotential bonding system via a wrist strap system." (ANSI/ESDS20.20-2007 section 8.2)

- Medical grade stainless steel interior expansion band will not cause allergic skin reactions for most people
- Non-flaking or scratching laminated insulator on all external surfaces protects wearers from electrical hazards
- · Superior contact with skin with more reliable path-to-ground
- Designed to be used with Dual-Wire Coil Cords and Dual-Wire Continuous Monitors
- Available in large, medium, or small sizes
- 4mm studs

ITEM	DESCRIPTION	CIRCUMEFERENCE MIN MAX	
63220	Dual-wire Metal Wrist Strap, with 6' Coil Cord, 4 mm studs, L	7" (177.8mm)	12" (304.8mm)
63221	Dual-wire Metal Wrist Strap, with 6' Coil Cord, 4 mm studs, M	6" (152.4mm)	11" (279.4mm)
63222	Dual-wire Metal Wrist Strap, with 6' Coil Cord, 4 mm studs, S	5.5" (139.7mm)	9" (228.6mm)
63230	Dual-wire Metal Wrist Strap, with 12' Coil Cord, 4 mm studs, L	7" (177.8mm)	12" (304.8mm)
63231	Dual-wire Metal Wrist Strap, with 12' Coil Cord, 4 mm studs, M	6" (152.4mm)	11" (279.4mm)
63232	Dual-wire Metal Wrist Strap, with 12' Coil Cord, 4 mm studs, S	5.5" (139.7mm)	9" (228.6mm)

See drawing 63500 for cord details



SEMTRONICS WRISTBAND, DUAL, METAL, 4MM SOCKET

ESD SYSTEMS.com

ESD SYSTEMS.COM 432 NORTHBORO ROAD CENTRAL MARLBORO, MA 01752 USA TEL. (508) 485-7390 FAX (508) 480-0257



DRAWING 63220 DATE: October 2008