



Product Group: Vishay Dale Resistors / June 2015

Author: Victor Santiago Tel: +1 402-563-6345 E-mail: <u>victor.santiago@vishay.com</u>

New CW...HE Axial Lead Wirewound Resistors Offer Reliable High-Energy Surge Protection to 106.5 J

Product Benefits:

- Silicone coated
- High-energy surge protection up to 106.5 J
- High-temperature operation to +350 °C
- Rugged, completely welded construction for increased reliability
- High power ratings from 3 W to 13 W at 25 °C
- 2,000-hour load-life stability of less than ± 3 % at +25 °C
- Resistances from 2 Ω to 938 Ω
- Tolerances of ± 5 % and ± 10 %
- TCR:
 - \pm 50 ppm/°C for resistance from 2.0 Ω to 9.9 Ω
 - \pm 30 ppm/°C for resistance of 10 Ω and above
- Available with both lead (Pb)-free and tin/lead terminations

Market Applications:

• Communication equipment, power supplies, metering and welding equipment, power tools, and appliances

The News:

Vishay Intertechnology introduces a new series of silicone-coated axial lead wirewound resistors that provides high-energy surge protection to 106.5 J and can be utilized in high-temperature operating conditions up to +350 °C.

- Provides overload and surge energy protection exceeding IEC 61000-4-5 (1.2 μs/50 μs)
- Offers superior short-term energy surge protection compared with standard wirewound devices
- High-temperature silicone coating allows for operating temperature ranges of -65 °C to +250 °C (characteristic U) and -65 °C to +350 °C (characteristic V)







Product Group: Vishay Dale Resistors / June 2015

The Key Specifications:

Model	Power rating P _{25 °C} (W)		Enorgy	Resistance
	Characteristic U +250 °C	Characteristic V +350 °C	Energy rating ¹ (J)	range (Ω)
CW02BHE	3.0	3.75	2.7 to 10.4	2.0 to 87.5
CW005HE	5.0	6.5	10.5 to 39.1	7.6 to 34.3
CW010HE	10.0	13.0	28.7 to 106.5	20.7 to 938

Note 1: Energy rating depends on resistance value

Availability: Samples and production quantities of the CW - High Energy series are available now, with a lead time of six to seven weeks for larger orders.

To access the product datasheet on the Vishay Website, go to http://www.vishay.com/ppg?30286 (CW - High Energy)

Contact Information:

THE AMERICASEUROPEASIA/PACIFICVictor SantiagoUwe KonradVictor GohVictor.santiago@vishay.comuwe.konrad@vishay.comvictor.goh@vishay.com