Customer Information Sheet

DRAWING No.: M80-815XXXX SHEET 2 OF 2 IF IN DOUBT - ASK NOT TO SCALE THIRD ANGLE PROJECTION ALL DIMENSIONS IN mm SPECIFICATIONS: 5.56 MAX -MATERIAL: (CONTACTS PER ROW - I) MOULDING = GLASS-FILLED POLYESTER. UL94V-O. BLACK CONTACTS = PHOSPHOR BRONZE LATCHES = BERYLLIUM COPPER FINISH: 5.98 MAX CONTACTS: 05 = 0.75 u GOLD 22 = 0.75 µ GOLD ON CONTACT AREA. 3.0 m 90/10 TIN/LEAD ON TAILS LATCH = 1.25µ NICKEL -(2.00 x No. OF CONTACTS ELECTRICAL: PER ROW) + 4.10 MAX CURRENT RATING (25°C) = 3.0A MAX. CURRENT RATING (85°C) = 2.2A MAX. 2.25 TYP -> 2.00 x (No. OF CONTACTS WORKING VOLTAGE = 800V AC/DC VOLTAGE PROOF = 1200V AC/DC PER ROW - 1) CONTACT RESISTANCE: INITIAL = 20 m Ω MAX. 4.75 -Ø0.80 MAX TYP AFTER CONDITIONING = 25 mO MAX. INSULATION RESISTANCE: INITIAL = 1000 $M\Omega$ MIN. Ø 0.90 MIN TYP AFTER CONDITIONING = 100 MO MIN. STRAIN RELIEF MECHANICAL: STRAP HOLES DURABILITY = 500 OPERATIONS (OPTIONAL) ENVIRONMENTAL: TEMPERATURE RANGE = -55°C TO +125°C PACKING: 2.00 ├~ 2.00 TYP TUBE 3.0 FOR COMPLETE SPECIFICATION, SEE COMPONENT SPEC COO5XX (LATEST ISSUE) 2.00 TYP Ø 0.50 TYP -> RECOMMENDED PCB LAYOUT | 5.07.14 | 12531 BRITISH STANDARD NAMF C/NOTE TO BS9525 F0033 ORDER CODE: ORDER CODE: APPROVED: S.BENNETT B5743-2XX-M-T-R M80-815XXXX NOTES: M. PLESTED CHECKED: TOTAL No. OF CONTACTS: TOTAL No. OF CONTACTS: I. 2-OFF STRAIN RELIEF STRAPS M80-0030006 DRAWN: D. BECK 04. 06. 08. 10. 12. 14. 16. 04, 06, 08, 10, 12, 14, 16, MAY BE USED WITH THIS CONNECTOR. 18, 20, 26, 34, 44 CUSTOMER REF.: 18, 20, 26, 34, 44 FOR RoHS COMPLIANT EQUIVALENT PRODUCT USE M80-863XXXX CONNECTORS. FINISH: -FINISH: -05 = GOLDASSEMBLY DRG: 22 = SELECTIVE GOLD + TIN/LEAD R = SELECTIVE GOLD + TIN/LEAD MATERIAL: **TOLERANCES** TITLE: DATAMATE DIL THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE $X = \pm 1$ mm VERTICAL MALE PC TAIL SEE ABOVE CONFIDENTIAL AND COPYRIGHT $X.X = \pm 0.25 mm$

www.harwin.com technical@harwin.com

PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION

 $X.XX = \pm 0.10$ mm $X.XXX = \pm 0.01$ mm ANGLES = ±5° UNLESS STATED

FINISH: S/AREA:

SEE ABOVE

mm²

ASSEMBLY - FRICTION LATCH

DRAWING NUMBER:

M80-815XXXX

SHT OF.