



JKL PART NUMBER	-A- LENGTH	LCD HIGH OUTPUT WHITE RGB COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) MINIMUM
BF2661-24B	61±1.0**	9,400°k x = .285 ± .03 y = .283 ± .03	490 @ 0°C	195	5 ± 1	30,000 TYP.	20,000
BF26180-24B	180±3.0		975 @ 0°C	390			
BF26188-24B	188±3.0		1115 @ 0°C	405			
BF26214-24B	214±2.0**		1150 @ 0°C	445			
BF26230-24B	230±3.0		1240 @ 0°C	495			
BF26240-24B	240±3.0		1290 @ 0°C	515			
BF26250-24B	250±1.5		1350 @ 0°C	540			

**NOTES:**

\* RATED LIFE IS DEFINED AS THE POINT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

\*\* LEAD LENGTH 15±3.0.

RATINGS AT 25°C UNLESS OTHERWISE SPECIFIED.

<p>METRIC THIRD ANGLE PROJECTION</p>	<p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0</p>	<p><b>JKL COMPONENTS CORPORATION</b></p>			
	<p>TITLE: <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b></p>				
<p>DRAWN BY L. WENGSTROM</p>	<p>APPVD BY L.R.</p>	<p>DATE 8/5/09</p>	<p>SIZE <b>A</b></p>	<p>FSCM NO. <b>55335</b></p>	<p>DRAWING NO. <b>BF 26-24B</b></p>
<p>- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED</p>			<p>SCALE NONE</p>	<p>RELEASED DATE 8/14/03</p>	<p>REVISION DATE 8/5/09</p>
<p>REV. NO.</p>	<p>DESCRIPTION/ECO NUMBER</p>	<p>APPVD DATE</p>	<p>REV. NO. <b>D</b></p>	<p>SHEET <b>1</b> OF <b>1</b></p>	

D	RATED LIFE HRS MINIMUM & 20,000 - & MARKUP	8/5/09
C	CORRECT x & y TOLERANCE	7/5/06
B	LENGTH TOLERANCE CHANGE ON BF26250-24B	2/3/06
A	ELECTRICAL CHANGES & ADD PART BF2661-24B	10/20/04
	RELEASED TO CAD MULTI LIST	8/14/03