

Flush-type connector - SACC-DSI-MINFS-3CON-M26 PCB - 1457830

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Sensor/actuator flush-type socket, 3-pos., 7/8", PCB mounting with M26 fastening thread



Key Commercial Data

Packing unit	1 STK
GTIN	4 046356 616942
GTIN	4046356616942

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C 85 °C (Socket)
Degree of protection	IP67

General

Rated current at 40°C	12 A
Rated voltage	250 V
Number of positions	3
Insulation resistance	\geq 100 M Ω
Coding	A - standard
Status display	No
Overvoltage category	II
Degree of pollution	3
Connection method	Solder pins
Mounting type	PCB mounting M26

Material

Flammability rating according to UL 94	НВ
Contact material	CuZn
Contact surface material	Au



Flush-type connector - SACC-DSI-MINFS-3CON-M26 PCB - 1457830

Technical data

Material

Contact carrier material	PUR	
Material, knurls	Zinc die-cast, nickel-plated	
Sealing material	Viton	

Standards and Regulations


Connection in acc. with standard	CUL
Flammability rating according to UL 94	НВ

Environmental Product Compliance


China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Dimensional drawing



Drilling diagram




Schematic diagram



Connector pin assignment

Dimensional drawing



7/8" flush-type socket

Approvals

Approvals

Approvals

EAC



Flush-type connector - SACC-DSI-MINFS-3CON-M26 PCB - 1457830

Approvals		
Ex Approvals		
Approval details		
EAC	EAC	B.01742

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com