

151-00932

Article Number: 151-00932

Description: Standoff Tape Clip, Panel Thickness .02"-.27", PA66HIRHS, Natural, 3000/box



Base Data	
Local Order Number	151-00932
Type	SOC11FTOVAL
Color	Natural (NA)
Features and benefits	<ul style="list-style-type: none"> <li>• Staggered fir tree branch design provides low insertion forces and high extraction forces.</li> <li>• Initial fir tree serves as a locating feature for assistance in blind assembly applications.</li> </ul>
Quantity Per	carton
Product Description	Bundling clips are designed to provide simple and easy methods of securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using bundle or cable ties. The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standard bundling clips are available as well as standoff and stud mount versions.
Short Description	Standoff Tape Clip, Panel Thickness .02"-.27", PA66HIRHS, Natural, 3000/box
Product Dimensions	
Length L (Imperial)	2.0"
Length L (Metric)	50.0mm
Length L2 (Imperial)	0.8"
Length L2 (Metric)	20.0mm
Height H (Imperial)	0.8"
Height H (Metric)	21.0mm
Panel Thickness Max. (Imperial)	0.27"
Panel Thickness Max. (Metric)	6.75mm
Panel Thickness Min. (Imperial)	0.02"
Panel Thickness Min. (Metric)	0.6mm
Mounting Hole Diameter D (Imperial)	0.24 x 0.48 "; 0.25 x 0.50 ", 0.25 x 0.5 " ;0.27 x 0.47"
Mounting Hole Diameter D (Metric)	7.0 x 12.0 mm
Mounting Hole Diameter D Min. (Imperial)	0.256"

151-00932



Product Dimensions	Mounting Hole Diameter D Max. (Imperial)	0.492"
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	3000
	Package Quantity (Metric)	3000
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces