

PRODUCT DATASHEET Sputnik series

last update 12/1/2016



Product number CA10298_SPUTNIK-R5

Family Sputnik Туре Assembly LED P5 Color Clear Diameter 26 mm Height 16.2 mm Style Round **PMMA** Optic Material Holder Material

Fastening ["tape"]

Status Production ready

FWHM 26 degrees
Efficiency cd/lm Gerber File Available

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.



PRODUCT DATASHEET Sputnik series

last update 12/1/2016

GENERAL INFORMATION

- Product series especially designed & optimized for P5 series of LEDs.
- Special care taken to make light distribution as uniform as possible.
- Lens material optical grade PMMA with high UV and temperature resistance. Allows use of high current and temperature conditions.

Please find more information about used material from below: http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20UL94_Yellow%20Card.pdf http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20PLEXIGLAS-Datasheet.pdf

Note! Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

