

## RAFIX 22 QR - Emergency stop pushbutton, reset by pulling

### 1.30.243.901/0300

Included: Ring nut with claw.



Switching position indication: In the non-operated condition, a green ring is visible on the side.

#### General information

Actuator	mushroom
Color of mushroom	opaque red
Form of collar	round

#### Dimensions

Dimensions of collar	ø 29.8 mm
Overall height	40.1 mm
Mounting depth with contact block without cable	56.4 mm
Mounting hole	ø 22.3 mm
Mounting grid	- mm

#### Mechanical design

Mounting	ring nut
Contact function	latching
Illuminability	no
Reset	by pulling
Lock type	-

#### Mechanical characteristics

Operating force max.	approx. 5 N for 1 switching element
Entsperr-Kraft	24 N with 2 contact blocks
Robustness max.	100 N
Robustness	acc. to IEC 60947-5-5

#### Other specifications

Operating life (operations)	100,000 cycle
Degree of protection from front side	IP65 (DIN EN 60529)
Ambient temp. operating min.	-25 °C
Ambient temp. operating max.	+70 °C
Storage temperature min.	-40 °C
Storage temperature max.	+80 °C
Environmental resistance	acc. to IEC 60068-2-14, -30, -33 and -78
ROHS compliant	yes
REACH compliant	yes

Panel cut-out to IEC 60947-5-1

