

AS5304
Magnetic Multipole Strip, MS20-50
Pole Length 2.0 mm, 50 poles

MAGNET SPECIFICATION

## General

This specification defines the dimensional and magnetic properties of a multi pole magnetic strip for use with the AS5304 magnetic linear motion and off-axis rotary angle encoder.

Material: rubber bonded Strontium Ferrite SrFe.

# 1 Dimensional Specification

Magnet Order # MS20- 50 on austriamicrosystems web shop, refer to Figure 1

Parameter	Symbol	Min	Тур	Max	Unit	Note			
Strip Width	W	100,84	101,6	102,36	mm	4.00" +/- 0.030"			
Strip Cut Length	S	4,62	5,0	5,38	mm	0.197" +/- 0.015"			
Strip Thickness	T	0,762	0,762	0,813	mm	0.030" +0.00" / - 0.002"			
Thermal expansion			49		x10 <sup>-6</sup> /K	Mechanical length expansion			
Density			3,4		g/cm <sup>3</sup>	estimated			
Delivery	4,00" x 0.030" x 200' Outdoor adhesive, cut thru .197".  Minimum 1 rolls (~ 12.000 strips).								

# 2 Magnetic Input Specification

Magnet Order # MS20- 50 on austriamicrosystems web shop, refer to Figure 1

Parameter	Symbol	Min	Тур	Max	Unit	Note
Pole length	Lp		2,00		mm	results in pole pair length of 4mm (50 poles @ 2,0mm, 2 border poles ~1,0mm)
Resolution	Res		25		μm	With AS5304 @ maximum interpolation
Pole length deviation				+/- 50	μm	Measured at Bz=0, all poles (Lp) within active region
Number of poles			50		poles	Excluding poles with L <lp at="" ends="" of="" strip<="" td="" the=""></lp>
Magnetic field amplitude @ 0.5mm distance	B <sub>pk</sub>		15		mT	Vertical component of the magnetic field strength in the center of the strip at 25°C
Amplitude variation				+/-1,5	mT	All poles within active region
Active Region to strip edge	А			0,5	mm	estimated
First Bz=0 position to strip edge	D1	TBD	1,0	TBD	mm	Tolerance estimated +/-0,25µm
Last Bz=0 position to strip edge	D2	TBD	1,0	TBD	mm	Tolerance estimated +/-0,25µm
Temperature range	Tamb	-18	25	80	°C	
Temperature drift	Tk <sub>Br</sub>		+0,2		%/K	Magnetic field temp. drift






Figure 1

#### Contact

## Headquarters

austriamicrosystems AG

A 8141 Schloss Premstätten, Austria

Phone: +43 3136 500 0 Fax: +43 3136 525 01

www.austriamicrosystems.com

### Magnet Supplier Information

ARNOLD Magnetic Technologies

107 Industry Road

Marietta, OH 45750

http://www.arnoldmagnetics.com/index.htm

## Copyright

Devices sold by austriamicrosystems are covered by the warranty and patent indemnification provisions appearing in its Term of Sale. austriamicrosystems makes no warranty, express, statutory, implied, or by description regarding the information set forth herein or regarding the freedom of the described devices from patent infringement. austriamicrosystems reserves the right to change specifications and prices at any time and without notice. Therefore, prior to designing this product into a system, it is necessary to check with austriamicrosystems for current information. This product is intended for use in normal commercial applications.

Copyright © 2008 austriamicrosystems. Trademarks registered ®. All rights reserved. The material herein may not be reproduced, adapted, merged, translated, stored, or used without the prior written consent of the copyright owner. To the best of its knowledge, austriamicrosystems asserts that the information contained in this publication is accurate and correct. However, austriamicrosystems shall not be liable to recipient or any third party for any damages, including but not limited to personal injury, property damage, loss of profits, loss of use, interruption of business or indirect, special, incidental or consequential damages, of any kind, in connection with or arising out of the furnishing, performance or use of the technical data herein. No obligation or liability to recipient or any third party shall arise or flow out of austriamicrosystems rendering of technical or other services.