

170-03191



Article Number: 170-03191

Description: Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, .38" Dia, AL/GF, Silver, 30/box

Base Data	Local Order Number	170-03191
	Type	BSHTTSW38SB
	Color	Silver (SR)
	Features and Benefits	<ul style="list-style-type: none"> <li>• A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.</li> <li>• Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.</li> <li>• Cuts with ordinary scissors for fast, easy application.</li> </ul>
	Quantity Per	box
	Product Description	Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance.
	Short Description	Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, .38" Dia, AL/GF, Silver, 30/box
Product Dimensions	Length L (Imperial)	4.0ft
	Length L (Metric)	1.22m
	Reel Length (imperial)	4.0ft
	Diameter D (imperial)	0.37"
	Diameter D (metric)	9.40mm
	Nominal Diameter (Imperial)	3/8"
	Nominal Diameter (Metric)	9.40mm
	Wall Thickness WT (Imperial)	.042"
	Wall Thickness WT (Metric)	1.06mm
Material and Specifications	Material	Glass fiber with aluminium foil (GF-AL)
	Material Shortcut	GF-AL

170-03191



Material and Specifications	Flammability	non flammable
	Operating Temperature	-76°F to +491°F (-60°C to +255°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	30
	Package Quantity (Metric)	30
	Customs Number(Schedule B)	7019901000