

111-25200

Article Number: 111-25200

Description: Heavy-Duty Cable Tie, 40.6" Long, 250lb Tensile Strength, PA66, Black, 25/pkg



Base Data	Local Order Number	T250XL0X2
	Type	T250XL
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Heavy duty design to offer higher tensile strength. • Buckle feature on head allows excess strap to be tucked away after installation.
	Quantity Per	bag
	Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Heavy-Duty Cable Tie, 40.6" Long, 250lb Tensile Strength, PA66, Black, 25/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		1115.0N
Length L (Imperial)		40.6"
Length L (Metric)		1030.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.49"
Width W (Metric)		12.5mm
Bundle Diameter Min. (Imperial)		0.47"
Bundle Diameter Min. (Metric)		12.0mm
Bundle Diameter Max. (Imperial)		12.0"
Bundle Diameter Max. (Metric)		305.0mm

111-25200

HellermannTyton

Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	Certification/Specification	UL ANSI/UL 62275
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	15.436kg